

# REACTION TO FIRE CLASSIFICATION REPORT $N^{\circ}$ 2012/018-1

(English report of classification report N°2012/018)

According to EN 13501-1 (2007) + A1 (2009)

# Notification by the French Government to the European Commission under n° NB 2401

Sponsor:

**BALSAN** 

Corbilly Arthon

36330 LE POINCONNET

**FRANCE** 

Product name:

Tufted carpets tiles 100% polyamide on bitumen backing

(Update)

Description:

Textile floor coverings (EN 1307 family)

(see detailed description in paragraph 2)

Date of issue:

16/05/2019

The indicated classification does not prejudge the conformity of marketed materials with the samples submitted to the tests and under no circumstances, this document should not be considered as type approval or certification of the product in the sense of the L 115-27 article of the consumption's code of the law dated June 3<sup>rd</sup> 1994.

The reproduction of this classification report is only authorised in its integral form. It comprises 5 pages

# 1. Introduction

This classification report defines the classification assigned to the above-mentioned product (s) in accordance with the procedures given in the NF EN 13501-1 standard: September 2007 & A1 (2009).

# 2. Details of classified product

# 2.1. Product standard

NF EN 14041 (2005): «Resilient, textile and laminate floor coverings - Essential characteristics.

# 2.2. Product description

Tufted pile carpet tiles of 50 cm x 50 cm 100% polyamide on bitumen backing (EN 1307 family).

Tested loose laid with a bonding system over a wood panel particle board without flame retarded classified  $C_{fl}$ -s1 with a density (680 ± 50) kg/m<sup>3</sup> and thickness (20 ± 2) mm.

Use surface: 100 % polyamide

Nominal mass per unit area: 4020 to 4885 g/m<sup>2</sup> Nominal effective pile thickness: 2,4 to 5,4 mm

#### 3. Test reports and tests results in support of this classification

# 3.1. Tests reports

Name of laboratory	Name of sponsor	Test report N°	Test method	
	BALSAN	RL 2016/610-1	NF EN ISO 9239-1	
CREE	Corbilly Arthon	RL 2017/767-1	NF EN 150 9239-1	
	36330 LE POINCONNET	RL 2016/610-2	NE EN 100 11005 0	
	FRANCE	RL 2017/767-2	NF EN ISO 11925-2	

# 3.2. Tests results

			Results	
Test method	Product	Number of tests	Parameters	Compliance parameters
NF EN ISO 11925-2			Fs ≤ 150 mm	Compliant
Surface exposure-15 secondes	L480	3	Ignition of the filter paper	Compliant

			Results	
Test method	Product	Number of tests	Parameters	Compliance parameters
NF EN ISO 11925-2			Fs ≤ 150 mm	Compliant
Surface exposure-15 secondes	BOLERO	3	Ignition of the filter paper	Compliant

				Results
Test method	Product	Number of tests	Parameters	Continuous parameters : mean value
NF EN ISO 9239-1	L480	Critical heat flux (kW/m² Smoke (% X min)	Critical heat flux (kW/m²)	4,6
	1.400		Smoke (% X min)	466,2

				Results
Test method	Product	Number of tests	Parameters	Continuous parameters: mean value
NF EN ISO 9239-1	BOLERO	Critical heat flux (kW/m Smoke (% X min)	Critical heat flux (kW/m²)	6,6
	BOLEKO		Smoke (% X min)	480,2

#### Classification and field of application

# 4.1. Reference of classification

This classification has been carried out in accordance with EN 13501-1:2007 & A1 (2009).

#### 4.2. Classification

Fire behaviour		Smoke production
C <sub>fl</sub>	-	s1

Classification: C<sub>fi</sub> - s1

# 4.3. Field of application

This classification is valid for the following end use applications:

Loose laid with a bonding system over a wood panel particle board without flame retarded classified C<sub>fl</sub>-s1 with a density (680  $\pm$  50) kg/m<sup>3</sup> and thickness (20  $\pm$  2) mm and over a fibre-cement A2<sub>fl</sub> or A1<sub>fl</sub> class with a density  $\geq 1350 \text{ kg/m}^3$ .

This classification is valid for the following product parameters:

- A nominal mass per unit area of: 4020 to 4885 g/m<sup>2</sup>
- A nominal effective pile thickness of: 2,4 to 5,4 mm

# The classification of the product family is valid for the following trademarks:

**ALIZE** 

**AVENUE** 

**BATIK** 

**BLOCK** 

**BOLERO** 

**BROOKLYN** 

**DELTA** 

**DESERT** 

**FACTORY** 

**FLOW** 

**FOREST** 

**INFINI COLORS** 

**JUNGLE** 

**KARMA** 

LAKE

L480

L480 SONIC LIGHT

**MAQUIS** 

**METROPOLITAN** 

**METROPOLITAN DISTRICT** 

**METROPOLITAN GRAFIK** 

**MISTRAL** 

**NIRVANA** 

**ODEON** 

ORIGAMI

PARK

AIN

PILOTE<sup>2</sup> PILOTE<sup>2</sup> SONIC LIGHT

PILODE 3D

RAIN RESONANCE

RIVER

ROCK

**SAVANE** 

SEASON

**SHADES** 

**SIMOUN** 

**SIROCCO** 

**SOHO** 

**STEPPE** 

STONE AGE

**STREAM** 

**SUMMER** 

**TOUNDRA** 

**TRACKS** 

**TRAMONTANE** 

**TRUST** 

**ZEPHYR** 

# 5. <u>Limitations</u>

This classification document does not represent type approval or certification of the product.

"The classification assigned to the product in this report is appropriate to a declaration of conformity by the manufacturer within the context of system 3 attestation of conformity and CE marking under the Construction Products Directive.

The manufacturer has made a declaration, which is held on file. This confirms that the products design requires no specific processes, procedures or stages (no addition of flame-retardants, limitation of organic content, or addition of fillers) that are aimed at enhancing the fire performance in order to obtain the classification achieved. As a consequence the manufacturer has concluded that system 3 attestation is appropriate.

The test laboratory has, therefore, played no part in sampling the product for the test, although it holds appropriate references, supplied by the manufacturer, to provide for traceability of the samples tested."

For the SARL C.R.E.T. The Technical Director Marc WELCOMME

End of the classification report