



Construction	Luxury Floating Flooring, Rigidcore
Plank Size	222.25mm x 1517.65mm
Tiles per Carton	6pcs / 2.02m ²
Total Weight	10148g/m ²
Wearlayer Thickness	0.55mm
Total Thickness	6.5mm (5mm + 1.5mm Acoustic Backing)
Backing	IXPE Acoustic Foam
Slip Resistance	P3 (EN 13893)
Fire Rating	CRF 8.4kW/m ² (ISO 9239-1)
Underfloor Heating	Suitable - See installation instructions for more information.
Wet Areas	Suitable (ISO 4760:2022)
Acoustic Properties	BCA Approved for High Rise Buildings
Resistance to Staining	Excellent (EN 423)
Abraision Resistance	Group T (EN 660)
Classification	Heavy Duty Residential Heavy Duty Commercial
Stair Rating	Suitable
Warranty	20 Year Residential Warranty 10 Year Commercial Warranty
Installation	Please contact Gilt Edge Industries for installation instructions. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	ISO 14001 Floorscore Certified



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.