

Westminster



Construction	Tufted Cut Pile Carpet
Yarn	100% Premium Solution Dyed Nylon
Width	4.0m
Standard Roll Length	30m
Yarn Weight	1200g/m ² / 36oz/yd ²
Total Weight	2496g/m ²
Pile Height	7.0mm
Total Thickness	9.5mm
Machine Gauge	1/10th
Primary Backing	Woven Polypropylene
Secondary Backing	FusionBac
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (EN 1815 / ISO 6356)
Fire Rating	AS ISO 9239-1
VOC Rating	Pass (GBCSA/GLP Criteria)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable - Maximum Temperature 37°C
ACCS Rating	REHD2 6 Stars incl. stairs / CHD3 Stars incl. stairs
Rating	Extra Heavy Duty Residential Heavy Duty Commercial
Stair Rating	Suitable
Warranties	20 Year Residential Warranty 10 Year Commercial Warranty
Installation	All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greentag Certified GreenStar Environmental Management ISO 14001 Quality Management ISO 9001 Occupational Health and Safety Management ISO 45001 Low VOC, solution dying uses no water, Eco-Wash™ Treatment



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A world of
perfect choices_